

Product Configuration Options

OrderCode:	IED-EP+ S/S24/Variant 4/D3300-C20005000000010-7D															
Platform: IED-EP+ S Smart line IED EP+			Type: S24 S24 Smart Line series				Configuration: Variant 4 MV line differential protection and autorecloser in 24HP industrial enclosure.									
Platform specific options	Position	0	1	2	3	4										
	Value	D	3	3	0	0										
Config specific options	Position	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14
	Value	D	2	0	0	0	5	0	0	0	0	0	0	0	1	0
Checksum	7D															
Detailed platform specific options																
Platform version															Position 0	
Current version															D	
Power Supply															Position 1	
24V															0	
48V															1	
60V															2	
110V															3	
220/230V															4	
I/O modules															Position 2	
24V															0	
48V															1	
60V															2	
110V (125V)															3	
220V															4	
110VAC															5	
230VAC															6	
Mounting methods															Position 3	
Flush mounting															0	
Din rail mounting															1	
Secondary language															Position 4	
None															0	
HUN															1	
GER															2	

RUS	3
ITA(N/A)	4
FRA	5
ROU	6
ESP	7
Detailed config specific options	
Configuration version	Position 0
Current version	C
Type of Power Supply module (S24)	Position 1
PSTP (2xTRIP)	2
Display type	Position 2
B&W	0
3.5" vertical	1
CPU first communication port	Position 3
N/A	0
Fiber optical ethernet MM/ST	1
Fiber optical ethernet SM/FC	2
Fiber optical Ethernet MM/LC	3
RJ-45	4
CPU secondary communication port	Position 4
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet SM/FC	2
RJ-45	3
Serial POF	4
Serial glass fiber	5
RS-485/422	6
Fiber optical Ethernet MM/LC	7
I/O module in position D	Position 5
N/A	0
O8	1
O12	2
O15	4
O6R5	5
R4	6

R8+00	7
R8+80	8
R12+0000	10
R12+4000	11
4xTRIP	17
I/O module in position E	Position 6
N/A	0
O8	1
O12	2
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R12+0000	10
R12+4000	11
RTD	13
CT module in position B	Position 7
CT+5151	0
CT+5153	1
CT terminal type	Position 8
Conventional	0
Ring-lug	1
VT terminal type	Position 9
Conventional	0
Type of LD communication	Position 10
Fiber optical SM SH/FC (0-50km)	0
Fiber optical MM/ST (0-2km)	1
IEC61850 protocol (additional charge)	Position 11
No	0
Yes	1
Customization service (additional charge)	Position 12
No	0
Yes	1
CyberProtect functionality	Position 13

No	1
Yes	2
SW option	Position 14
N/A	0