

Product Configuration Options

OrderCode:	IED-EP+ S/S24/Variant 7/D3300-B200005000010-54													
Platform: IED-EP+ S Smart line IED EP+		Type: S24 S24 Smart Line series				Configuration: Variant 7 High-impedance differential protection in 24HP rack size. (Numbers of binary I/O in the standard configuration: 5BOut, 6Bin.)								
Platform specific options	Position	0	1	2	3	4								
	Value	D	3	3	0	0								
Config specific options	Position	0	1	2	3	4	5	6	7	8	9	10	11	12
	Value	D	2	0	0	0	0	5	0	0	0	0	1	0
Checksum	54													
Detailed platform specific options														
Platform version														Position 0
Current version														D
Power Supply														Position 1
24V														0
48V														1
60V														2
110V														3
220/230V														4
I/O modules														Position 2
24V														0
48V														1
60V														2
110V (125V)														3
220V														4
110VAC														5
230VAC														6
Mounting methods														Position 3
Flush mounting														0
Din rail mounting														1
Secondary language														Position 4
None														0
HUN														1

GER	2
RUS	3
ITA(N/A)	4
FRA	5
ROU	6
ESP	7
Detailed config specific options	
Configuration version	Position 0
Current version	B
Type of Power Supply module (S24)	Position 1
PSTP (2xTRIP)	2
Display type	Position 2
B&W	0
3.5" vertical	1
CPU first communication port	Position 3
N/A	0
Fiber optical ethernet MM/ST	1
Fiber optical ethernet SM/FC	2
Fiber optical Ethernet MM/LC	3
RJ-45	4
CPU secondary communication port	Position 4
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet SM/FC	2
RJ-45	3
Serial POF	4
Serial glass fiber	5
RS-485/422	6
Fiber optical Ethernet MM/LC	7
I/O module in position C	Position 5
N/A	0
O8	1
O12	2
O15	4
O6R5	5

R8+00	7
R8+80	8
R8+C0	9
R12+0000	10
I/O module in position D	Position 6
N/A	0
O8	1
O12	2
O15	4
O6R5	5
R4	6
R8+00	7
R8+80	8
R12+0000	10
R12+4000	11
4xTRIP	17
Number of differential currents	Position 7
1	0
3	1
CT terminal type	Position 8
Conventional	0
Ring-lug	1
IEC61850 protocol (additional charge)	Position 9
No	0
Yes	1
Customization service (additional charge)	Position 10
No	0
Yes	1
CyberProtect functionality	Position 11
No	1
Yes	2
SW option	Position 12
N/A	0